MOL ATF Synt 3H

synthetic automatic transmission fluid

Product benefits

- outstanding oxidation and thermal stability
- very low pour point
- excellent anti-wear properties and friction characteristic
- wide range of application in automatic transmissions

Applications

MOL ATF Synt 3H high performance automatic transmission fluid (ATF) suitable for automatic transmissions, power steering units meeting performance requirements of most modern cars, vans and other commercial vehicles where the operating manual specifies the below-listed or lower performance levels.

Specifications and approvals

GM Dexron-IIIH
Ford Mercon
Ford Mercon V
MAN 339 Type V-2
MAN 339 Type Z-2
ZF TE-ML 14B
Voith H55.6336
Allison C-4

Product description

MOL ATF Synt 3H premium multifunctional automatic transmission fluid is manufactured from very high quality synthetic base oil with advanced additive system meeting the highest quality requirements. The product has been developed for extreme long-drain intervals.

Due to its advanced formula it has outstanding oxidation stability, provides high level of wear and corrosion protection, resulting long drain interval even under at heavy load or wide operating temperature conditions.

Its favorable cold viscosity due to the synthetic composition provides proper operation of the hydraulic control units even in the winter period and forms stable, permanently loadable lubricating film in wide range of the operating temperature.

The optimum frictional characteristic ensures precise and noiseless shifting and reduces the energy losses in the gearbox.

Typical properties

Properties	Typical values
Density at 15°C [g/cm3]	0,853
Kinematic viscosity at 40°C [mm2/s]	35,0
Kinematic viscosity at 100 °C [mm2/s]	7,8
Viscosity index	208
Pour point [°C]	-42
Flash point (Cleveland) [°C]	200

The characteristics in table are typical values of the product and do not constitute a specification.

Manufactured and distributed by: MOL-LUB Ltd.
Technical service: H-1117 Budapest, Október huszonharmadika u. 18.
H-1986 Budapest, MOL Plc. Tel: +36-1-4640236 Fax: +36-1-4640304 E-mail: lubricants@mol.hu
Latest revision: 2009.06.19 09:04 Version 004.000.000

MOL ATF Synt 3H

synthetic automatic transmission fluid

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.
For further details please read the Material Safety Data Sheet of the product.
Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.
In the original container under the recommended storage conditions: 60 months
Inflammability hazard: Grade IV.
Recommended storage temperature: max. 40°C

Ordering information

SAP code and packaging:
13006905 60 l steel drum
13006906 216.5 l steel drum

Order booking (toll-free):

Phone: 80/201-331 (between 07-16 h weekdays)

Manufactured and distributed by: MOL-LUB Ltd.
Technical service: H-1117 Budapest, Október huszonharmadika u. 18.
H-1986 Budapest, MOL Plc. Tel: +36-1-4640236 Fax: +36-1-4640304 E-mail: lubricants@mol.hu
Latest revision: 2009.06.19 09:04 Version 004.000.000